KUCHINDA COLLEGE, KUCHINDA

(Estd. 1964, Accredited by NAAC)

Registered under the Societies Registration Act No. XXI of 1860 No. 3353/43 of 1965-66

Ph./FAX/Off.: (06642) 220030 Web: www.kuchindacollege.in

E-mail: kuchindacollege@yahoo.co.in

G-mail: kuchindacollegekuchinda@gmail.com

AT/P.O.- KUCHINDA-768222

Dist. Sambalpur (Odisha)

S. E. Railway Bamra / Jharsuguda

Ref. No.3.7-3.125 Date 24/04/25



From: PRINCIPAL Kuchinda College Kuchinda

Kuchinda College, Kuchinda **Quotation Call Notice**

Sealed quotations are hereby invited from Authorized Firms/Suppliers to reach the undersigned by registered/Speed post on or before 15.05.2025 for the procurement of the following items for IT infrastructure funded by Higher Education Department, Govt. of Odisha. Interested firms are required to quote the price of each item with GST separately. Item wise specifications are attached on Annex-B.

ITEMS to be procured:

- 1. Desktop
- 2. UPS
- 3. MFM Printer
- 4. LED TV (65 inches)
- 5. Wireless Mice and Camera for virtual meeting
- 6. Internet- Facility

The undersigned reserves the right to cancel the quotations without giving any reason thereof.

PIN No. 768222

Dist-Sambalpur

Items	Cassification	
binet Form Factor	Specification Tower/Micro Tower (15.1 to 26 Litres)	
ipset Number	Intel H670/Intel® H770 or higher Chipset	
ocessor Make		
	Intel	
ocessor	x86 64-bit architecture	
ocessor Generation	13 Or higher	
ocessor Description	Intel Core i3 or higher	
rocessor Number	Intel Core i3 13100 or higher Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8	
umber of Cores and Threads per Processor	Threads or higher	
perating System	Windows 11 Home Factory Preloaded	
AM Size (GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
RAM Expandability up to (using spare DIMM Slots in GB)	64 GB or higher	
ntegrated Graphics	Intel UHD Graphics 770 or higher	
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Yes	
Type of Drives used to populate the Internal Bays	NVMe SSD	
Total HDD Capacity (GB)	NA .	
Total SSD Capacity (GB)	512GB NVMe SSD	
Optical Drive	Optional	
Drive Bays	Two 3.5" (2.5") HDD	
Slots for Upgradation	1 PCI Express 4.0 x16, 1 PCI Express 3.0 x1, 1 PCI (Full Height), 2 M.2 slots for WLAN & SSD LAN: Integrated 10/100/1000M	
LAN	Library 1 headphone/microphone combo; 3 Super Speed USB	
Ports and Connectors	SGbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0	
Firmware Trusted Platform Module	TPM 2.0	
Hardware Security lock slot	Security lock slot 180-260Watt Internal power supply with minimum 90%	
Power Supply	efficiency Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM in	
	required. OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate	
Certification	Microsoft Windows, Energy star 8.0 certified	
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate of products at the time of participation of the Bid.	
L. A.Mouro	USB Keyboard: USB Optical Mouse	
Keyboard Mouse Monitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM	
Years of Warranty	3 Year Onsite Warranty	



		nteractive UPS Specifications
SI. No.	Feature	General Specifications
1	UPS Capacity (total)	600VA/360W
2	Input Voltage	230 VAC nominal
3	Input Frequency	45 - 65 Hz
4	Brownout Transfer	145 VAC typical
5	Over-voltage Transfer	290 VAC typical
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)
7	Frequency – On Battery	50Hz typical
8	Transfer Time	@50 Hz : 6 ms typical, 10 ms max
9	Air Ventilation	Should have Side and Back Honey bee Perforation for heat dispersion
10	Protection from Humidity & Dust	UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also
		Full time, 160 joules
13	AC Surge Protection Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference.
	Type (maintenance-free)	12V, 7,2 Ah
	Typical recharge time	4-6 hours
16	Operating Temperature	0°C to 40°C
18	Storage Temperature	-15°C to 45°C
19	3 power outlets	With battery backup and surge protection
	Power Cord	1.2 meters
20	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)
22	Runtime for Workstation PC (100W ±15W)	113 min (normal mode)
23	Battery Saver (to save on battery life)	Thru toggle button on front panel
24	Certification	BIS
25	Designed and Manufactured in India	Yes
26	Warranty	2yeasrs .

	Generic	
Description of Stores	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter	
Core Function	Print, Scan and Copy	
Print Technology	Laser	
Cartridge Technology	Composite Cartridge	
Type of Printing	Monochrome (Black)	
RAM Size (MB)	256	
Storage Capacity (in GB)	0	
Features	Fax OC Windows Server	
Operating System Compatibility	Fax Windows 10 and Above, Linux, Mac OS, Windows Server	
	Printing	
Print Paper Size	A4 and Legal	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	26 to 30	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	Not Applicable in	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size-Mono (in PPM)	Not Applicable	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Color (in PPM)	Not Applicable	
Auto Duplexing Printing/Coping (2-sided Feature)	Yes	
	Scanning	
Maximum Scan Area (Platen/Flatbed Size)	A4 and Legal	
A4 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpl	11 to 20	
Scan To Functions	Email	
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 20	
, i	COPYING	
Reduction and Enlargement	Yes	

	PAPER HANDLING
al- Un	Tooday (ADF)
riginal Document Feeder Type	Automatic Document Feeders (ADF)
or Scanning and Copying)	
or Scanning and Copying)	
	24 1- 40
seder Capacity (Humbor of	31 to 40
theets) (For Scanning and	
Seedon)	
Copying)	
Table 1 - Table 1	1 10 3 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Number of Main Paper Tray	
	101 to 200
Total Paper Tray Combined	101 10 200
Capacity (Number) at 75 GSM	
Oakasi, (The second secon
Dimage Tray Facility	No
Bypass Tray Facility	0
If Yes, Bypass Tray Capacity	
Connectivity	USB Port,Ethernet Port,Wi-Fi
Connectivity	USB Cable
Accessories Provided	USB Cable
Accessories	Performance
Sould of the	700
Minimum Yield of the	
Cartridge/Ink/Toner supplied	
IL Machine as Del 13/130/120	
19752/2017 for Black (Number	
of Prints)	
- Viold of the	0
I Linimiim Tield Ol die	
Minimum Yield of the	
I M-L/TABAR SUDDING	
Cartridge/Ink/Toner Supplied	
with Machine as per IS/ISO/IEC:	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of	
with Machine as per IS/ISO/IEC:	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	10,001 to 20,000
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number	
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	10,001 to 20,000
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number	10,001 to 20,000
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz 1300
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental Minimum Operating	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz 1300
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz 1300
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental Minimum Operating Temperature (Degree C)	10,001 to 20,000 POWER Single Phase AC 220 - 240 V, 50 - 60 Hz 1300
Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints) Minimum Duty Cycle (Number of Prints/Month) Power Supply Maximum Power Consumption (in Watt) Environmental Minimum Operating	POWER Single Phase AC 220 - 240 V, 50 - 60 Hz 1300

		TO SEE SEE SEE SEE SEE SEE SEE SEE SEE SE
		65
POTENTIAL DESCRIPTION OF THE PARTY OF THE PA	Screen Size	350Nits or better
100	Brightness (cd/m³)	1200:1
STATE OF STATE	Contrast Ratio	400,000:1
	Dynamic Contrast Ratio	8.0
galara est	Response Time (ms)	3840 x 2160
ral Features	Display resolution (H x V, pixels)	Yes (HDR10, HLG)
	HDR (High Dynamic Range) compatiblity	16:9
1. 23 W. T. 18	Aspect Ratio	Yes
· 大学 计图 2011	Portrait/Tilt Compatibility	Frame Dimming
经验证据包括	Dimming type	LCD
	Display Device	IPS
	Panel Type	Direct LED
		69%
	Backlight type	16/7
isplay features	Color gamut (NTSC)	1 %
ispiay realares	Operation time	178 (89/89) degree
-	Haze (%)	178 (89/89) degree
-	Viewing Angle (Right/Left)	1/8 (8)/85/
-	Viewing Angle (Up/Down)	4096 x 2160p (24, 50, 60 Hz), 3840 x 2160p (24, 25, 30, 50,
	HDMI Signal	3840 x 2180p (20, 50, 60 H 60 Hz), 1080p (30, 50, 60 H 1080/24p, 1080i (50, 60 H 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
		Down Firing
	Speaker Position	10W + 10W
CONTRACTOR OF THE STATE OF THE	Audio Power Output	
Audio Specs	1 Contract Contract	Yes (Simple Pro settings men
The state of the s	Pro settings	Yes
	HDMI auto wake-up	Android TV
Professional	Operating System	16GB
features	On-board Storage (GB)	3GB
The Water of	RAM	Yes
A 2 00 YEAR OLD THE	Wi-Fi Certified	Integrated
1.5-25	Wireless LAN	MPEG1:MPEG1/MPEG2
Network Specs	USB playback codecs	PS:MPEG2/MPEG2 WEBM:AV1/AC4/088/AAC
Convenience features		WEBM:AV1/AC4/0687
	On Screen Clock	Yes
	Sleep Timer	Yes To July
	On/Off Timer	And the second s
	Chromecast built-in	TOWN YES
	Chromecast built-ui	Yes Yes
Washington and the second	Apple Aliray IP Control	Yes
	RS-232C Control	Yes
Control Specs	HDMI-CEC	HDCP2.3 (for HDMI1/2/
Control spe	HDMP-CEC HDCP	1 (Side, Mini jack)

Inputs and outputs	HDMI inputs total	William (3Side)	
	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)	
	Digital Audio Output (s)	1 (Side)	
	USB ports	2 (Side)	
1.13	Ethernet inputs	14 (Side) 11 1 (Side)	
Design features	VESA® Hole Pitch (W x H)	300 x 300 mm	
Environment Specs	Rated Power Consumption	226W	
	Power Consumption (in Standby)	0.5 W	
	Dynamic Backlight Control	## O Yes Yes Yes	
	Power Saving Mode / Back Light Off Mode	Yes	
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm	
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm	
- 1	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm	
125-1265E	Weight of TV without Stand	20.4 kg	
Weight	Weight of TV with Stand	21.3 kg	
	Weight of Package Carton (Gross)	28 kg	

.

01:48 AM G#44149013

E core tendestriponting com

Olfers OST Benutits Become a Seller Bulk Order FAQs Di Jrack Order 🗣



@ ma biscours

Industrybuying

Search Products by hise sky category heard eld

a Login

Quantity 1

Share -

Home / IT Security / Computer Accessories / WEBCAM / Logitech Master Series Grophite M

Logitech Master Series Graphite MX Brio 4K Uttra Hd Web Camera, 960-001548

Visit the Logitech Slove

AVAILABLE OFFERS

LIED +14-995 0 862-015 Order

224,719 (Incl of all laxes)

\$20,999 ·18% 047

EMI starts at #2202/month No Cost EMI available [MI options

Bulk quantity Discounts!!

TARLE	PATROCES IN	DISCOVERS
		price per
Select	Quantity	piece(incl of oil
马出	19.5	(oxes)
0	2-3	F23,98014
U		
0	4-5	£23,740 53
0	8-7	£23,500 93
U	880150	
_	# mode	173,34119





Bu sreps within 5 days

FEATURES

Get up to \$4,000° on a min, order value of \$6,496

Oet up to \$3,500° on a min order value of \$8,455 First-time B28 users only T&C opply

FIRST-TIME GET USERS ONLY TEC OPPRY

Country of Origin

Switzerland

Connectivity

use-c to Use-C

Focus Type

More Logitach WIBCAM products

Advanced Autolocus

Package Contains

MORE WIECAM PRODUCTS

MX Brio, Mount Clip with Removable Adapter, USB-C to C 3 0 Cable, User Documentation

O Check Delivery Details

Enter Pulcasa

ADD TO CART

C



BUY NOW

0

PREPAID

Avoltable

PART COD

Unavailable

COD "

Available

Avolloble Return

RETURN

period 7 days



Warranty as per brand



100% Original Products



payments



protection

Brands

SPECIFICATIONS

DESCRIPTION

Country of Origin

Switzerland

Connectivity

USB-C to USB-C Cable

FOCUS TYPE

MX Bno. Mount Clip with Removable Adapter, USB-C to C 3 9 Cable, User Documentation

Package Contains

Dual Beamforming

Microphone Type

98 mm

WICH

4x Digital Toom

Type of Product

Web Camera MOCRETO-ARGRET

Part No

44 mm

Height Welgh

137 g

Lens Type

Gloss

interloce

Color

U18 3 0 Graphite

Resolution mage Sensor 4x/30 tps, 1080p/80 fps

85 MP Sony STARVIS 960-001548







1/3